



DEFEND NV1050

SPECIFICATIONS

MODEL

NOVAERUS DEFEND NV1050
2-wheeled base + handle, 5-speed fan setting

ELECTRICAL RATING

Single phase, 230 VAC, 50 Hz

POWER CONSUMPTION

137 – 331 W

DIMENSIONS + WEIGHT

93.0cm (h) x 58.0cm (w) x 48.0cm (d)
51 kg

AIR FLOW

181 – 906 m³/hr (107 – 533 CFM)

AREA COVERED

1000Sq. Ft.

NOISE LEVEL

47.9 – 75.1 dBA at unit
38.5 – 62.9 dBA at 1m away

FILTERS

Stage 1: Pre-filter (M5)
Camfil® Part No. 715-00-0203
400 (h) x 400 (w) x 48 (d) mm

Stage 2: HEPA filter (H13)
Camfil® Part No. 715-00-0163
400 (h) x 400 (w) x 110 (d) mm

Stage 3: Carbon filter (G4)
Camfil® Part No. 715-00-0162
400 (h) x 400 (w) x 50 (d) mm

Designed for rapid remediation in large spaces and situations with high risk of infection, the Novaerus Defend NV1050 uses patented ultra - low energy plasma technology combined with a triple stage Camfil® filter system to provide a combined solution for air dis-infection and particle removal.

AREA COVERAGE

18.6 – 92.9 m² (4 air changes per hour)
37.2 – 185.8 m² (2 air changes per hour)

VOLUME TREATMENT

45 – 226 m³ (4 air changes per hour)
90 – 452 m³ (2 air changes per hour)

Nivritti AST LLP

17/8, West Mada Church Road, Royapuram,
Chennai, Tamil Nadu, India - 600013

Ph: +91 98410 69000
marketing@nivast.in